

FYREWASH® F3 RR

ROCHEM

Powerful.Efficient.Reliable

EFFECTIVE GAS TURBINE COMPRESSOR CLEANING



Developed specially to meet & clean Rolls Royce Gas Turbine Compressors

Rochem offers a range of powerful specialist compressor cleaning chemicals exhibiting outstanding performance, they're designed for all types of fouling and meet current OEM and environmental standards worldwide. All of the Rochem FYREWASH® chemical range is suitable for both on-line and off-line washing.

FYREWASH® F3 RR PRODUCT DESCRIPTION

FYREWASH® F3 RR was developed to give the maximum possible cleaning efficiency and effectiveness from a non-solvent chemical. FYREWASH® F3 RR has superior cleaning qualities that are non-hazardous, user-friendly and highly biodegradable water based cleaner which now sets the standard against which the performance and cost effectiveness of all other true nonsolvent water-based gas turbine compressor cleaners can be judged.

Approved & meets Rolls Royce specification for online & offline washing. CEFAS Approved for use offshore.

FYREWASH® F3 RR can be used with any on-line or off-line injection system, designed specifically for your gas turbine types.

FEATURES and BENEFITS

Safely and effectively cleans compressors on-line and off-line.

Extremely effective non-solvent cleaner.

Meets the most stringent requirements of gas turbine manufacturers.

Ideal for light and frequent on-line washing of any type of industrial, marine or aviation gas turbine to maintain in-service output and fuel efficiency.

Ideal for off-line cleaning due to high cleaning efficiencies.

Backed by Rochem's unique high value product liability insurance.

On-line cleaning reduces damaging shutdown/start-up thermal cycles and starter wear and tear.

PROPERTIES

APPEARANCE: Colourless.

SHELF LIFE : 5 years.

TYPICAL PROPERTIES: Density 1.01g/ml@ 20°C,
PH 8.5 (20% in water).

DILUTION: FYREWASH® F3 RR concentrate with four (4) parts of water into a stable solution.

APPLICATION: FYREWASH® F3 RR can be used with any on-line or off-line injection system.

WATER RINSE: Online washing best practice is to perform rinse flush with demin water. Offline washing rinse until effluent runs clear.

ANTIFREEZE: Add antifreeze below +10°C, FYREWASH® F3 RR is compatible with Methanol, Propylene Glycol, Ethylene Glycol. Rochem manufacture a superior freeze point depressant, Rochem FPD, please contact Rochem for further information.



FYREWASH® F3 RR

ROCHEM

Powerful.Efficient.Reliable

EFFECTIVE GAS TURBINE COMPRESSOR CLEANING



Find out more about our FYREWASH® range:

FYREWASH® F1

A HIGH PURITY HYDROCARBON SOLVENT & SURFACTANT FORMULATION FOR HEAVY DUTY ONLINE AND OFFLINE COMPRESSOR CLEANING.

FYREWASH® F2

A LOW FOAM WATER BASED CLEANER CONTAINING A RENEWABLE SOLVENT FOR ONLINE AND OFFLINE COMPRESSOR CLEANING.

FYREWASH® F3

ENVIRONMENTALLY FRIENDLY WATER BASED DETERGENT FOR ONLINE AND OFFLINE COMPRESSOR WASHING.

FYREWASH® F3

Oil & Gas

ENVIRONMENTALLY FRIENDLY WATER BASED DETERGENT FOR ONLINE AND OFFLINE COMPRESSOR WASHING ON OFFSHORE OIL & GAS PLATFORMS.

FYREWASH® F3 RR

ENVIRONMENTALLY FRIENDLY DEVELOPED SPECIALLY FOR ROLLS ROYCE GAS TURBINE COMPRESSORS.

FYREWASH® F4

HIGHLY BIO-DEGRADABLE WATER BASED DETERGENT FOR ONLINE AND OFFLINE COMPRESSOR CLEANING.

HEALTH & SAFETY

FYREWASH® F3 RR is a safe and highly biodegradable chemical. However, for off-line, crank wash cleaning all chemical solution and rinse water drainage should be collected and disposed of properly no matter what type of chemical is being used.

EC Hazard rating: Xi. Irritant. US NFPA rating 1,1,0
Protective Measures: Non-hazardous but avoid frequent prolonged direct contact with skin to prevent possibility of de-oiling skin and wear eye protection as a matter of course when handling any chemical.

Spillage: Absorb large spillages with sand or earth. Flush away small spillages with water.

Fire: Use foam, carbon dioxide, dry chemicals, sand or earth.

MANAGEMENT SYSTEM

TARIFF CODE: 34029090 EUROPE
ISO14001: 2015 & ISO9001: 2015

ENVIRONMENTAL

All chemical solution and rinse water drainage should be collected and disposed of correctly. Adhere to your local environmental regulations.

LOGISTICS

Packaging

25 lt (6.5 USG) pails and 210 lt (55 USG) drums, 1000 lt IBC.

Shipping

No restrictions. Classified as non-hazardous for international transport by road, sea and air.

Storage

Store in a cool, well ventilated dry place in tightly closed drums. Avoid temperature fluctuations.

Please contact Rochem for full information on your on-line or off-line compressor washing requirements.

